



MASSEY FERGUSON



38-46 HP

MF 1700

Neat, nimble and easy to use compact tractor



FROM MASSEY FERGUSON

Specifications

Engine	
Power @ 2600 rpm	
Cylinders/Capacity	
Fuel tank capacity	
Transmission type	
Power take-off	
Engagement	
Rear PTO Speeds	
Mid PTO	
Wheels and tyres	
'Standard' agricultural tyres	
'Standard' turf tyres	
Rear axle	
Differential Lock	
Brakes, internal, wet disc	
3-point linkage, Hook end Cat 1	
Draft control system	
Lift capacity	
Hydraulic pump capacity	
Spool valves	
ROPS, MID folding	
Weights and dimensions	
Weight	
Overall length/height/width	
Wheelbase	
Min. ground clearance	
Other	
Cab option	
Heat and ventilation	
Air conditioning	
Pivoting bonnet, Power stg, road lighting	

	MF 1740	MF 1747
ISO hp (kW)	38(28)	46(33.8)
No./cc	3 (turbo) / 1498	4/2197
litre	40	53
HC	● Hydrostatic (HST)	● Hydrostatic (HST)
A	● Mechanical 12 x 12	● Mechanical 12 x 12
	Independent	Independent
rpm	540/540 Eco	540/540 Eco
HC	●	●
A	○	○
Front	8.00-16	9.5-16
Rear	13.6-24	13.6-28
Front	212 x 80 D15	212 x 80 D15
Rear	355 x 80 D20	355 x 80 D20
	●	●
	●	●
	●	●
HC	-	-
A	●	●
Kg	1270	1580
Litre/min	74.3	74.3
	2	2
A	●	●
Kg HC	1680	1958
Kg A	1528	1810
mm (HC min)	3475/2200/1440	3455/2325/1645
mm	1770	1900
mm	310	310
	HC only	HC only
	●	●
	●	●
	●	●



Left hand reverse shuttle lever



Cruise, engine response controls



Independent PTO engagement



Mechanical joystick

MF 1700

- 2 NEW models 1740 (38 hp) and MF1747 (46 hp) available
- Mechanical 12x12 synchro shuttle or hydrostatic transmissions versions
- Available in cab and platform

Key features

- New hydrostatic features include shuttle lever on left hand side with electrical cruise control, response and max speed adjustment
- 75 l/min hydraulic pump flow
- 2 spool valves standard with joystick lever
- 540/540 Eco independent PTO.
- 2 door cab with air conditioning as standard.